

MATERIAL SAFETY DATA SHEET

SECTION 1- CHEMICAL, PRODUCT AND COMPANY INFORMATION

Product Trade Name: Cabinet Rescue (Trademark)

Product code: DT-43

Chemical Name: Water based paint

Chemical Family: Acrylic

HMIS RATING: Health..... 1
Flammability..... 0
Reactivity..... 0

DOT: Not regulated

Emergency contact: Tel.: 1-800-433-5998

Technical/MSDS information: Tel.: (941) 278-5495

Distributor: Decotime, Inc., P.O. Box 62041, Ft. Myers, FL 33906-2041

Date of preparation: July 25, 2003 Supercedes: April 28, 1998

Reason: Added product use and HMIS rating. Modified Section 6.

Product use: Decorative coating for various substrates

SECTION 2- COMPOSITION, INFORMATION OR INGREDIENTS

<u>Ref.</u>	<u>Ingredients</u>	<u>% by wt.</u>	<u>CAS Number</u>	<u>Carcinogen*</u>
1.	Water	15-40	7732-18-5	
2.	Titanium Dioxide	10-30	13463-67-7	
3.	Acrylic emulsion	10-30	mixture	
4.	Nepheline Syenite	5-10	37244-96-5	
5.	Propylene glycol	5-10	57-55-6	
6.	Diethylene glycol- monobutyl ether	1-5	112-34-5	

* Carcinogens: O=OSHA; A=ACGIH; N=NTP; I=IARC

Ref. SARA 311/312 SARA 313

1.	Not Hazardous	Not Hazardous
2.	Not Hazardous	Not Hazardous
3.	Not Hazardous	Not Hazardous
4.	Not Hazardous	Not Hazardous
5.	Not Hazardous	Not Hazardous
6.	Listed	Listed

OCCUPATIONAL EXPOSURE LIMITS HAVE BEEN ESTABLISHED FOR THE FOLLOWING MATERIALS:

<u>Ref.</u>	<u>ACGIH TLV</u>	<u>OSHA PEL</u>
1.	NA	NA
2.	10 mg/m ³ 10 mg/m ³	
3.	NOT ESTAB.	NOT ESTAB.
4.	10 mg/m ³ 5 mg/m ³	
5.	50 PPM	NOT ESTAB.
6.	NOT ESTAB.	NOT ESTAB.

NOT ESTAB.= NOT ESTABLISHED NA= NOT APPLICABLE
PRODUCT STATUS RELATIVE TO THE U.S. EPA TOXIC SUBSTANCES CONTROL ACT: All chemical substances in this product are listed on the U.S. TSCA Inventory or are otherwise exempt from TSCA Inventory reporting requirements.

SECTION 3- HAZARD IDENTIFICATION

EFFECTS OF OVEREXPOSURE FROM:

> INGESTION: Harmful if swallowed.

> EYE CONTACT: Causes eye irritation but will not injure eye tissue.

> SKIN CONTACT: May cause slight skin irritation.

> INHALATION: Vapor and/or spray mist may be harmful if inhaled.

SIGNS AND SYMPTOMS OF OVEREXPOSURE:

Redness, itching or burning sensation may indicate excessive eye contact. Dryness, itching, cracking, burning, redness and swelling are conditions associated with excessive skin contact. Dizziness may be associated with inhalation of spray vapors or mists. Nausea or vomiting may be symptoms resulting from ingestion.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:

Not applicable.

SECTION 4- FIRST AID MEASURES

> INGESTION: Do not induce vomiting. Consult a physician.

> EYE CONTACT: Rinse with clean water for 15 minutes. Get medical attention if irritation persists.

> SKIN CONTACT: Wash with water.

> INHALATION: Remove to fresh air.

WARNING: This product contains a chemical known to the State of California to cause cancer.

DECOTIME, INC.

SECTION 5- FIRE FIGHTING MEASURES

> FLASHPOINT: Not applicable. Water based paint.

> UPPER EXPLOSION LIMIT (UEL): Not available.

> EXTINGUISHING MEDIA: Extinguishers appropriate for surrounding fire.

> UNUSUAL FIRE & EXPLOSION HAZARDS: Closed containers may explode or burst (due to the build-up of steam pressure) when exposed to extreme heat.

> Water spray may be ineffective. Water spray may be used to cool closed containers exposed to extreme heat. Firefighters should wear self-contained breathing apparatus and full protective clothing.

SECTION 6- ACCIDENTAL RELEASE MEASURES

> STEPS TO TAKE IN CASE OF SPILL: Ventilate area. Collect-up and return spilled paint to original containers. Take-up residual paint with inert absorbent material and place in empty container for disposal.

> WASTE DISPOSAL METHOD: Dispose of in accordance with local, state and federal regulations. This product is not a hazardous waste under RCRA regulations (40 CFR 261), but may be regulated by other jurisdictions.

SECTION 7- HANDLING AND STORAGE

> HANDLING & STORAGE PRECAUTIONS: Protect from freezing.

SECTION 8- EXPOSURE CONTROLS AND PERSONAL PROTECTION

PERSONAL PROTECTIVE EQUIPMENT FOR:

> EYE PROTECTION: Wear safety glasses.

> SKIN PROTECTION: Wear protective clothing to prevent skin contact. Gloves should be constructed of neoprene rubber, nitrile rubber or latex. Recommendations for skin protection is based on infrequent contact with this product. For frequent contact or total immersion, contact a manufacturer of protective clothing for appropriate chemical impervious equipment.

> RESPIRATORY PROTECTION: Overexposure to vapors or spray mist may be prevented by ensuring proper ventilation controls, vapor exhaust and fresh air entry. A NIOSH-approved air purifying respirator with the appropriate chemical cartridges or a positive-pressure air supplied respirator may also reduce exposure.

> OTHER EQUIPMENT: Clean contaminated clothing and shoes.

SECTION 9- PHYSICAL AND CHEMICAL PROPERTIES

> BOILING POINT: >212 Degrees Fahrenheit.

> FREEZING POINT: <32 Degrees Fahrenheit.

> SOLUBILITY IN WATER: Partial. Emulsified water based paint.

> VAPOR PRESSURE: 2.3KPa

> VAPOR DENSITY (air=1): Not applicable.

> EVAPORATION RATE (n-butyl acetate=1): 0.36

> % VOLATILE BY VOLUME: 60%-70%

> SPECIFIC GRAVITY: 1.3

> pH: 8-9

> ODOR AND APPEARANCE: Opaque liquid with a mild odor characteristic of the chemical family and any solvents listed in sec. 2.

SECTION 10- STABILITY AND REACTIVITY

> STABILITY: This product is normally stable and will not undergo hazardous reactions.

> INCOMPATIBILITY: Avoid contact with strong oxidizing agents.

> HAZARDOUS DECOMPOSITION PRODUCTS: May produce the following hazardous products when exposed to extreme heat or flame: Carbon monoxide, carbon dioxide, smoke.

> HAZARDOUS POLYMERIZATION: Will not occur.

DISCLAIMER: All information, recommendations and suggestions contained herein are based on tests and data believed to be reliable. Since the use of this information, opinions and the conditions of use of the product are not within the control of the supplier, it is the user's obligation to determine the conditions for safe use of this product.

THIS IS THE END OF THE MSDS FOR: Cabinet Rescue™